

## 7287 Lockbolt Tool

### Hydropneumatic

The 7287 is able to place heavy duty rivets with just one press of the trigger. With an extended stroke and a quick cycle time this tool combines speed and power making it the ideal tool for batch and line production.

#### Features

- Hydro-pneumatic split tool for Monobolt® fasteners and lockbolts
- Extended stroke and pull force
- Installation of large fasteners with single pull action
- Short cycle time
- Lightweight placing head
- Remote intensifier mounted on castors
- 3 m hose length
- Wide choice of directly interchangeable 722 model nose assemblies to suit the access restrictions of the application
- Places a wide range of fasteners in one stroke
- Does not require second actuation
- High placement speed
- Can offer labour cost savings
- Can increase assembly capacity
- Reduces operator fatigue
- Flexible use in the assembly line
- Can be fitted with a collar cropper to remove installed Avdelok® lockbolts

#### Technical Data

<b>Pistol weight</b>	: 1.47 kg (without equipment) < 2.5kg (with equipment)
<b>Total weight</b>	: 40kg (without equipment)
<b>Stroke</b>	: 29 mm (min. under load) 32 mm (free cycling)
<b>Cycle Time</b>	: 1.7 sec (approx.)
<b>Air Supply Pressure</b>	: 5 - 7 bar
<b>Free Air Volume</b>	: 3.5 litres at 5.5 bar
<b>Noise Level</b>	: 75 dB
<b>Vibration</b>	: < 2.5 m/s <sup>2</sup>

*For accessories options, contact  
Gripwell Sales for assistance*



#### Placing Capability

- Avdelok®, Avtainer® and Monobolt® fasteners up to  $\varnothing$  3/8" (10 mm)
- Avbolt® fastener up to  $\varnothing$  5/16" (8 mm)
- All other lockbolts up to  $\varnothing$  5/16" (8 mm)
- Avseal® II sealing plugs up to  $\varnothing$  14 mm

